

Product Information Sheet

everroll® Tone – 4mm

1. Application	Fitness Sports Leisure & Commercial Retail Education Flooring		
2. Product	Name of Product	: everroll® Tone	
	Colour	: Berlin, Nome, Kush, Goa, Lhasa, Auckland, Sydney, Perth	
	Material	: elastic pre-manufactured rubber flooring mat made from EPDM granulates and selected rubber granulates, bound with polyurethane	
	Thickness	: 4mm	
3. Technical Data	Specific Weight	: 1060 kg/m ³	
	Weight per m ²	: 4.24 kg	
	Tensile Strength	: 1.80 N/mm ²	following DIN EN ISO 1798
	Elongation at Break	: 95% following	DIN EN ISO 1798
	Tear Resistance	: 13.5 N/mm	following DIN ISO 34-1
	Coefficient of friction	: ≥ 0.3 μ	EN 14 041
	Temperature Resistance	: - 40° C up to 115° C	
4. Notice	The above mentioned test data are based on periodical laboratory testing of test specimen taken from the actual manufacturing process and show the average values measured. The publishing of these technical data does not relieve the user of the necessity to test the relevant product for physical fitness based on a specific application. As the final use and application of our products are out of our control, this is the sole responsibility of the buyer / end user. All of our products do carry a warranty against manufacturer's defects according to our standard terms and conditions of sale. Due to deviations in raw materials, external influences like temperature and humidity variations, and the fact that this data relates to a resilient material, the above mentioned values are subject to vary up to +/- 25%.		

ANH NGOC THANH TRADING COMPANY LIMITED (ANTRADE CO., LTD.)



HCM office: R. 5.03, 5th Fl., Phuong Tower,

31C Ly Tu Trong Str., Ben Nghe W., Dist.1, HCMC.

Tel: (+84) 28 38257622 / 28 38257623

Website: www.antrade.vn || Hotline: +84 93 366 2138 || Email: sales@antrade.vn

HN office: R. 701, 7th Fl., 131 Bui Thi Xuan Str.,

Hai Ba Trung District, Ha Noi City, Vietnam.

Tel: (+84) 24 63289487 / 24 39749263