

Cleaning & maintenance instructions

2018

Somplan Collections

HOMOGENEOUS VINYL

Modern day-room cleaning aims at a reduction of wet cleaning procedures and their replacement by drier cleaning techniques. For example is the usage of pre-impregnated mops laundered centrally as well as full usage of appropriate machines to prefer. This makes work easier for the cleaning staff, is more effective and influences the environment as little as possible. Less cleaning chemicals and less fresh water are used.

This way the cleaning procedures yield improved results of a constant quality. Centra flooring by Tarkett has a PUR reinforced wear layer which minimizes the use of cleaning chemicals.

INITIAL SITE CLEANING

- Always protect the floor with thick paper, hard board or similar during the construction period. An initial site clean is always to be recommended before using the new flooring:
 - Lightly soiled floors: Vacuum, sweep or damp-mop the area to remove loose dirt and building dust. A combined scrubber/dryer with brushes or white/yellow pads are very effective to clean large areas. Use solution with low pH, to be able to pick up dust from construction work..

GENERAL ADVICE

- Resilient floors are damaged by solvents.
- Wipe up any spilt oil immediately because it may damage the surface.
- Black rubber wheels and rubber feet can discolour.
- All chair legs must have protective feet.
- Remember that light colours need more frequent cleaning

DAILY CLEANING



- Daily Cleaning:** Dry- or damp-mopping



- Machine cleaning:** In order to achieve good results, clean the floor gently with a combined scrubber-dryer machine and medium hard brushes or preferably red pads.
- Cleaning chemicals:** If wet cleaning is necessary, use a neutral floor cleaner. Wet-rooms may necessitate occasional cleaning with acidic cleaning agents, pH 3 to 5, in order to remove residual lime and soap.
- Warning!** Always follow dosage instructions carefully!
- Removing marks:** Treat marks immediately. Use white/red nylon pads moistened with methylated spirits, cleaning spirit or neutral detergent.
- Wipe one more time with clean water.

PREVENTIVE CARE

- Use correctly dimensioned entrance matting to remove dirt in the entrance area. About 80% of all the dirt on the floor that has to be cleaned off is brought in from outside. And 90% of that can be avoided by effective and correctly dimensioned entrance matting.
- The less dirt that comes in through the entrance, the lower the maintenance requirements.

PERIODICAL CLEANING



- Heavy wear and soiling necessitates machine cleaning**
Apply the cleaning solution (a fairly strong cleaning agent, pH 10-11 after dilution) to the flooring and allow to penetrate for 5-10minutes. Clean the floor using a heavy single scrub machine and red cleaning pad. Vacuum away the dirty water immediately. Rinse with clear water. Allow the floor to dry and then apply the maintenance system as per the instructions above.

ANH NGOC THANH TRADING COMPANY LIMITED (ANTRADE CO., LTD.)

HCM office: R. 5.03, 5th Fl., Phuong Tower,
31C Ly Tu Trong Str., Ben Nghe W., Dist. 1, HCMC.
Tel: (+84) 28 38257622 / 28 38257623

HN office: R. 701, 7th Fl., 131 Bui Thi Xuan Str.,
Hai Ba Trung District, Ha Noi City, Vietnam.
Tel: (+84) 24 63289487 / 24 39749263

Website: www.antrade.vn

Hotline: +84 933 662138

Email: sales@antrade.vn



Tarkett